

LATERAL FLOW CONTACT TEST APPARATUS

5

Background Of The Invention

1. *Field of the Invention*

The invention relates generally to urinalysis devices.

2. *Description of Prior Art and Related Information*

Chemical contact test devices generally include a test agent, such as a test pad containing one or more chemicals, adapted to come into contact with a fluid sample to be tested. Specific chemicals are provided in the test agent to react with the certain chemicals being detected in the fluid sample. If the chemicals being tested for are present in the sample, a chemical reaction occurs, resulting in a visible color change in the testing agent. By comparison with a color chart, the resulting color on a pad indicates whether certain chemicals are present. Such chemical "contact" tests include devices which may be used, for example, in urinalysis to aid in diagnosis and monitoring the progress of disease, to screen a population for asymptomatic, congenital or hereditary diseases, and to monitor the effectiveness or complications of therapy. In addition, it may be used to test for chemical adulteration of body fluids, such as urine.

As drug screening becomes increasingly prevalent, a greater need exists to detect adulterants used to thwart such drug tests. Adulterants, such as bleach for

example, may interfere with the mechanism of the drug test, causing the test to report false results. A major problem with present drug screening, therefore, is the inaccuracy of a drug test due to the possible usage of adulterants.

Adulteration testing devices have been developed to address this uncertainty.

- 5 Conventional adulteration testing devices include a dipstick containing several chemical contact test pads which is immersed into the fluid sample being tested. A major problem with conventional adulteration testing is that it consists of an additional test that must be performed with a device that is different and separate from the drug testing device. Hence, technicians are compelled to divide a liquid sample into multiple portions, increasing the probability of mix-ups and messy spills. A further disadvantage of the dipstick, as with other conventional urinalysis tests, is that once the fluid sample contacts the testing agent, chemicals from the testing agent may leach into the fluid sample. Thus, all of the fluid sample within a container is contaminated and rendered obsolete for further testing. If the fluid sample is not initially divided into separate containers, testing for adulteration may render the entire sample obsolete, thus requiring the donor to give a new sample and the technician to repeat testing.

- 20 In addition to drug testing and adulteration testing, the same contamination problem exists with current urinalysis in other types of applications, such as in the diagnosis of disease. Once a portion of a fluid sample contacts the testing agent, chemicals from the testing agent leach into that portion making it unusable for any further tests. This often leads to additional expense and inconvenience as the donor must resubmit a sample while additional materials and labor is required for retesting the new sample.

Furthermore, conventional urinalysis test devices include the dipstick which indicate the presence of certain substances, such as glucose or blood. In addition to the contamination problem, a conventional dipstick requires a large volume of urine held in a container of sufficient depth to allow a necessary length of the stick to be immersed.

- 5 If a particular sample from a donor is small, testing the urine with a conventional urinalysis device may be precluded. Additional time, expense and inconvenience are incurred as the donor is compelled to resubmit a larger sample.

Summary Of The Invention

In one aspect, a lateral flow test strip assembly is provided for testing a liquid sample. The assembly comprises a support, a contact detection pad coupled to the support, and a reagent-free absorbent strip coupled to the support. As used in the specification and recited in the claims, the contact detection pad comprises an absorbent carrier and a reagent composition adapted to detect one or more substances which may be found in the liquid sample.. Furthermore, as a “contact” detection pad, the reagent composition impregnated therein is adapted to detect such chemicals upon contact, as opposed to antibody-antigen binding associated with immunoassay strips. Thus, the reagent composition in the contact detection pad is not intended to be transported from one region of the pad to another region where a binding compound is disposed. The contact detection pad, therefore, excludes immunoassays, but comprises all other reagent compositions.

In a preferred embodiment, the contact detection pad comprises a contact urinalysis pad to detect one or more substances which may be found in urine. The contact urinalysis pad may comprise an adulteration pad to indicate whether a urine sample has been adulterated. The contact urinalysis pad may further comprise a bodily substance detection pad to detect bodily substances.

The reagent-free absorbent strip is in fluid communication with the contact urinalysis pad and is adapted to receive the urine and to communicate the urine to the contact urinalysis pad. As distinguished from immunoassays, the absorbent strip does not contain any antigens, antibodies, or any other reagents for that matter. Thus, the “reagent-free” absorbent strip primarily serves to direct the urine sample from a front,

receiving portion to a rear end portion, where the urine is then communicated to the contact urinalysis pad.

The assembly further comprises means for preventing the urine from traveling beyond the contact urinalysis pad. The preventing means preferably comprises a liquid impervious pad coupled to the support. The liquid impervious pad is disposed adjacent to the contact urinalysis pad at the opposite end from the absorbent strip. The preventing means further comprises a gap between the contact urinalysis pad and the liquid impervious pad.

In a preferred embodiment, the absorbent strip is in fluid communication with the contact urinalysis pad. More particularly, the absorbent strip directly contacts and overlaps a portion of the contact urinalysis pad. The contact urinalysis pad may comprise an adulteration pad. The contact urinalysis pad may also comprise a bodily substance detection pad that detects for bodily substances other than antigens or antibodies.

In another aspect, a chemical test system is provided and adapted to test for the presence of multiple chemicals in a liquid sample. This multi-test system comprises a first sub-assembly and a second sub-assembly. The first sub-assembly, or base assembly, comprises a first backing, a first contact detection pad coupled to the first backing, and a first absorbent strip coupled to the first backing. The first contact detection pad includes an absorbent carrier and a reagent composition adapted to chemically react with a first chemical. The first absorbent strip is in communication with the first contact detection pad. The second sub-assembly, or add-on assembly, comprises a second absorbent strip in communication with the first absorbent strip, a

second contact detection pad in communication with the second absorbent strip, and a second backing disposed between the second contact detection pad and the first absorbent strip.

The multi-test system further comprises a first liquid impervious pad coupled to the first backing and disposed adjacent to the first contact detection pad opposite to the first absorbent strip. The first liquid impervious pad is spaced apart from the first contact detection pad. The multi-test assembly further comprises a second liquid impervious pad coupled to the second backing and disposed adjacent to the second contact detection pad opposite to the second absorbent strip. The second liquid impervious pad is spaced apart from the second contact detection pad.

In a preferred embodiment, at least a portion of the first contact detection pad and at least a portion of the second contact detection are exposed. The first contact detection pad preferably comprises a first urinalysis pad. The second contact detection pad preferably comprises a second urinalysis pad.

In a further aspect, a chemical testing device is provided. The device comprises a housing, a contact urinalysis pad including a reagent composition adapted to react with one or more specific chemicals upon contact, and an absorbent strip in communication with the contact urinalysis pad. The housing includes means for viewing at least a portion of the contact urinalysis pad. In a preferred embodiment, the housing comprises a cassette. The housing comprises an aperture open to at least a portion of the absorbent strip. The device further comprises a lateral flow immunoassay strip disposed substantially within the housing.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

In another preferred embodiment, the housing comprises a lid adapted to be removably coupled to a vessel. The device further comprises means for introducing a liquid sample in the vessel to the absorbent strip. The contact urinalysis pad preferably comprises an adulteration pad or a bodily substance detection pad. The device further comprises a lateral flow immunoassay strip disposed substantially within the housing.

A method for performing urinalysis is also provided. The method comprises receiving the liquid sample with a reagent-free absorbent strip, providing an urinalysis pad with a composition dispersed therein and adapted to test for a target substance upon contact, laterally flowing the liquid sample to the urinalysis pad with the reagent-free absorbent strip, and providing a detectable response as a result of detection of the target substance. The method further comprises assaying for an immunological chemical with a lateral flow immunoassay strip and preventing the liquid sample from traveling beyond the urinalysis pad.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

A method for manufacturing a combined drug testing and adulteration testing device is provided as well. The method comprises providing a housing, disposing a drug test strip in the housing, disposing in the housing a reagent-free absorbent strip in communication with a contact detection pad, and preventing fluid communication between the drug test strip, on the one hand, and the absorbent strip and the contact detection pad, on the other hand. The method further comprises providing a stop to prevent a sample liquid absorbed in the contact detection pad from traveling beyond the contact detection pad. Providing a housing comprises forming apertures open to the drug test strip and the absorbent strip.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

In conclusion, a test strip assembly for detecting the presence of a substance in liquid sample comprises a contact detection pad in communication with a reagent-free absorbent strip. The absorbent strip receives the liquid sample and communicates it to the contact detection pad via lateral flow. The absorbent strip and contact detection pad are adhered to a support. A liquid impermeable pad is disposed adjacent to and spaced apart from the contact detection pad to prevent any further travel of the sample. Further add-on assemblies may be coupled to the base test strip assembly. The test strip assembly may be disposed in a housing along with a drug test strip to form a device that performs multiple types of tests. Methods for assaying and manufacturing are also provided.

The invention, now having been briefly summarized, may be better visualized by turning to the following drawings wherein like elements are referenced by like numerals.

Brief Description Of The Drawings

FIG. 1 is a perspective view of a test strip according to the invention;

FIG. 2 is an exploded view of the test strip of FIG. 1;

FIG. 3 is a cross-sectional view taken along lines 3-3 of FIG. 1;

5 FIG. 4 is a partially exploded, side-view of a multi-test system according to the invention;

FIG. 5 is a perspective view of the multi-test system of FIG. 4;

FIG. 6 is an exploded view of a preferred embodiment of a test device incorporating the test strip;

10 FIG. 7 is a perspective view of a removable lid of the test device of FIG. 6;

FIG. 8 is an exploded view of a further preferred embodiment of a test device incorporating the test strip;

FIG. 9 is a perspective view of the test device of FIG. 8;

15 FIG. 10 is a flow diagram illustrating a preferred method of detecting a target substance in a liquid sample ;

FIG. 11 is a flow diagram illustrating a preferred method of manufacturing a combined drug testing and contact detection pad device.

20 The invention and its various embodiments can now be better understood by turning to the following detailed description wherein illustrated embodiments are described. It is to be expressly understood that the illustrated embodiments are set forth as examples and not by way of limitations on the invention as ultimately defined in the claims.

Detailed Description Of The Preferred Embodiments

In FIGS. 1, 2 and 3, a first preferred embodiment of a lateral flow contact test assembly 10 is illustrated. The assembly 10 comprises a support, or backing, 20. The backing 20 has a supporting side, or surface, 22, an opposite resting side, or surface, 24, a front end 26 and a back end 28. The backing 20 comprises a front portion, 31, a midportion 33, and a rear portion 35.

A contact detection, or contact indicator, pad 40 is disposed on the midportion 33 of the backing 20 on the supporting side 22. A first surface 44 of the pad 40 is coupled to the backing 20. The contact detection pad 40 includes an outwardly facing second surface 45 opposite to the first surface 44, a front end 46, and a back end 47.

In a preferred embodiment, the contact detection pad 40 comprises a contact urinalysis pad 40 having an absorbent carrier 42 with a reagent composition disposed therein. The reagent composition is reactive with a certain chemical or chemicals which may be found in urine. The contact urinalysis pad 40 may comprise an adulteration pad having a reagent composition or compositions to indicate whether a liquid sample has been adulterated. The adulteration pad may provide such an indication by detecting certain adulterants which are not normal constituents of urine, such as bleach or glutaraldehyde, or by detecting an abnormal presence of a normal constituent of urine, such as creatinine.

The contact urinalysis pad 40 may also comprise a bodily substance detection pad having a reagent composition or compositions to detect bodily substances other than antigens or antibodies, such as glucose, bilirubin, ketone, blood, protein,

urobilinogen, nitrite, leucocytes and more. The bodily substance detection pad may also measure pH and specific gravity of the urine.

The contact detection pad 40 is to be distinguished from conventional immunoassays which include colored antigens or antibodies disposed adjacent to a receiving end of a strip. In one such conventional immunoassay, the colored antigens along with any other antigens in the sample diffuse up the strip and react with a line of antibodies immobilized on the strip. If no antigens are present in the sample, the colored antigens are captured by the predisposed lines of antibodies on the strip, yielding a colored line which indicates a negative result. If antigens are present in the sample, such antigens are captured by the antibodies. This prevents the colored antigens from being captured by the antibodies, thus leaving the line colorless to indicate a positive result.

In contrast, the contact detection pad 40 according to the invention does not include antibodies intended to bind with antigens. Furthermore, the contact detection pad 40 is not a lateral flow strip in that it does not include predisposed chemicals designed to be carried along the pad, by a wicking liquid sample, from one region to another region where it may bind with an immobilized, second reagent composition. Instead, the reagent composition in the contact detection pad 40 provides a detectable response simply upon contact with the liquid sample if a certain substance is present. It is to be expressly understood that the contact detection pad 40 may be provided to detect substances in any liquid sample in addition to urine. Therefore, even though the contact detection pad 40 comprises a contact urinalysis pad in a preferred embodiment, the contact detection pad 40 is not limited to detecting substances in urine alone.

As discussed further below, the liquid sample is brought into contact with urinalysis pad 40 by a reagent-free absorbent strip 50. The absorbent strip 50 is disposed in fluid communication with the contact urinalysis pad 40. The absorbent strip 50 preferably contacts the urinalysis pad 40 directly such that the liquid sample wicking through the absorbent strip 50 is conveyed, or communicated, to the urinalysis pad 40. It is to be understood that one or more intermediary, reagent-free absorbent carriers may be disposed in between the absorbent strip 50 and the urinalysis pad 40 while still maintaining fluid communication therebetween. Therefore, the absorbent strip 50 may be in fluid communication with the urinalysis pad 40 whether or not the absorbent 50 directly contacts the urinalysis pad 40.

In a preferred embodiment, the absorbent strip 50 is coupled to the backing 20 and disposed over its front portion 31 and midportion 33. The absorbent strip 50 has a front end 52, a front receiving portion 53 adjacent thereto, a back end 54 and an adjacent rear portion 55. The absorbent strip 50 is thus adapted to receive a liquid sample at its receiving portion 53 and to convey the liquid sample from the receiving portion 53 to the rear portion 55 via capillary action.

The rear portion 55 of the absorbent strip 50 directly contacts the urinalysis pad 40 as shown in FIG. 3. Thus, the absorbent strip 50 is preferably disposed over a portion of the outwardly facing surface 45 in order to better facilitate fluid communication between the absorbent strip 50 and the contact urinalysis pad 40. The rear portion 55 of the absorbent strip 50 overlaps only a front portion of the contact urinalysis pad 40 such that the uncovered portion of outwardly facing surface 45 is visible.

The absorbent strip 50 is distinguished from those in immunoassays in that it does not contain any antigens, antibodies, or any other reagents for that matter. Thus, the "reagent-free" absorbent strip 50 primarily serves to direct the urine sample from the front, receiving portion 53 to a rear end portion 55, where the liquid sample is then
5 communicated to the contact detection pad 40.

In FIGS. 1, 2 and 3, a liquid impervious pad 60 is coupled to the rear portion 35 of the backing 20. The impervious pad 60 is thus disposed adjacent to the back end 47 of the contact urinalysis pad 40 and slightly spaced apart therefrom to form a gap 65. In FIG. 3, the impervious pad 60 and the gap 65 collectively form a stop to prevent the liquid sample absorbed in the contact urinalysis pad 40 from traveling any further beyond the rear 47 of the urinalysis pad 40. In the case of a positive test result which yields a specific color in the urinalysis pad 40, this stop also serves to prevent the coloration of the contact urinalysis pad 40 from diffusing. It is to be understood that a variety of mechanisms may be employed to form the stop. For example, a hydrophobic line composed of wax or plastic may be disposed.
10
15

In the preferred embodiment, the absorbent strip 50, contact urinalysis pad 40, and the liquid impervious pad 60 are adhered to the support 20.

In operation, a liquid sample, such as urine, is introduced to the absorbent strip 50 at its receiving portion 53. Through capillary action, the liquid sample wicks through
20 the absorbent strip towards the rear end 54. Thus, the absorbent strip 50 conveys the liquid sample from the receiving portion 53 to the rear portion 55 where the liquid sample is then communicated to the contact detection pad 40. The liquid sample is brought into contact with, and absorbed into, the contact detection pad 40. If a certain

target substance, such as an adulterant or a specific bodily substance, is present in the liquid sample, a chemical reaction occurs between the chemical in the liquid sample and the predisposed chemical or chemicals in the contact detection pad 40. Thus, a chemical reaction results from the contact of the liquid sample with the contact detection pad 40, which contact is accomplished by the lateral capillary flow provided by the reagent-free absorbent strip 50.

In the field of urinalysis, it will be appreciated that what was once a device-to-sample test (i.e., the test device, such as a dipstick, had to be brought to the liquid sample) has been reversed in direction, i.e., sample-to-device (i.e., the liquid sample is brought to the device). One advantage of this reversal in direction is that the reagent composition in the urinalysis pad 40 will not leach out and contaminate any remaining liquid sample since the only portion affected will be the small amount introduced to the assembly 10. Thus, if the remaining urine is stored in a separate container or in a separate compartment of the same container, as will be shown below in a preferred embodiment, such remainder will remain unaffected and available for further testing. This conveniently obviates the need for any additional samples from the donor by preventing contamination of the remaining, untested urine.

A further advantage of the test strip assembly 10 is that only a small amount of urine is necessary for testing. Unlike the dipstick which must be immersed in a substantial volume of liquid sample, only a few simple drops of urine are required by the present assembly for testing. This minimizes inconvenience and embarrassment for the donor who may only be able to submit a small sample. Having to deal with only a few

droplets of urine instead of a large volume also reduces exposure to the technician and facilitates improved sanitation.

It will further be appreciated that what was once a "contact" only test has been transformed to a lateral flow test, one advantage of which is that one or more assemblies may be coupled to a base assembly 10 to form a multi-test system 200 as shown in FIGS. 4 and 5. In the following description of the multi-test system 200, the term "first" generally refers to components of the base assembly 10 while the term "second" generally refers to components of the add-on assembly 100.

In FIGS. 4 and 5, the strip assembly 10 of FIGS. 1-3 serves as the base strip assembly to which a second strip assembly 100 is coupled. The second strip assembly 100 comprises a second reagent-free absorbent strip 150 that is in fluid communication with the first reagent-free absorbent strip 50 of the base assembly 10. The second absorbent strip 150 is coupled to a second backing 120. The second backing 120 is substantially shorter than the first backing 20 of the base assembly 10. The second backing 120 is coupled to the first absorbent strip 50, preferably by adhesion with two-sided tape 170. A second contact detection pad 140 is coupled to the second backing 120.

The second contact detection pad 140 includes a composition preferably to test for the presence of a substance different than the substance being tested for by the base contact detection pad 40. It will be appreciated that countless combinations may be formed. For example, both contact detection pads 40, 140 may comprise adulteration pads, each testing for a different adulterant. Alternatively, both contact detection pads 40, 140 may comprise bodily substance detection pads with each pad

detecting a different bodily substance. As a further example, one contact detection pad 40 may comprise an adulteration pad while the other contact detection pad 140 comprises a bodily substance detection pad. It will be appreciated that the number of combinations increases exponentially with each new add-on assembly.

5 Similar to the base assembly 10, the second absorbent strip 150 directly contacts the second contact detection pad 140 and, preferably, overlaps a front portion of the second contact detection pad 140, leaving the remaining portion thereof uncovered. A second liquid impervious pad 160 is coupled to the second backing 120. The second liquid impervious pad 160 is disposed adjacent to and spaced apart from a back end 147 of the second contact detection pad 140.

10 In a preferred embodiment, the back end 128 of the backing 120, which is also the rearmost end of the entire add-on assembly 100, is flush with the back end 54 of the first absorbent strip 50 so as to not obstruct visual access to the first contact detection pad 40. Alternatively, the back end 128 of the backing 120 may be disposed in front of the back end 54 of the first absorbent strip 50, but preferably not any further past the back end 54.

15 With the rear portion 55 of the first absorbent strip 50 covering a front portion of the top of the first urinalysis pad 40, it will be appreciated that the first absorbent strip 50 serves as both a support for the add-on assembly 100 as well as a shield for the first
20 contact detection pad 40. A second gap 165 in conjunction with the second liquid impermeable pad 160 serve to prevent any liquid sample from traveling beyond the back end 147 of the second contact detection pad 140.

In operation, a liquid sample is introduced to the first absorbent strip 50 is communicated to the first contact detection pad 40 as previously described above. As the liquid sample is conveyed from the receiving portion 53 to the rear portion 55 of the first absorbent strip 50, the liquid sample is communicated to the second absorbent strip 150. In the add-on assembly 100, the liquid sample is communicated to the second contact detection pad 140. The second gap 165 and second liquid impervious pad 160 prevent the liquid sample from traveling beyond the back end 147 of the second contact detection pad 140.

The scalability of the present invention will be appreciated as further add-on assemblies may be provided with their corresponding absorbent strip in communication with the base absorbent strip 50 either directly or indirectly through an intermediary reagent-free absorbent strip or strips. An advantage of this lateral flow multi-test system 200 is that several tests may be performed with a single system that requires merely a few drops of urine.

A further advantage of the strip assembly 10 according to the invention is that it may be incorporated into a testing device that also assays for immunological chemicals, such as antigens and antibodies, to determine, for example, illegal drug use.

In FIGS. 6 and 7, the strip assembly 10 according to the invention may be disposed within a compartment of a housing 310. In a preferred embodiment, the housing 310 comprises a removable lid, or cap, adapted to be coupled to a vessel 326, such as a cup, for holding a liquid sample. The strip assembly 10 is disposed in a compartment 320 within the lid 310. The lid 310 further comprises a separate compartment 322 for holding a conventional drug test strip 330, such as a lateral flow

immunoassay strip. The receiving portion 53 of the absorbent strip 50 is bent downward to exit a port 324 in the lid 310. Thus, the receiving portion 53 of the absorbent strip 50 along with a receiving portion 331 of the drug test strip 330 protrude downwardly through the lid 310 so as to receive the liquid sample carried thereto by the scoop 341.

It will be appreciated that both adulteration testing and drug testing is concurrently provided by a single device. The contact urinalysis pad 40 is disposed in the compartment 320 and is viewable through the translucent or transparent lid 310. Similarly, the drug test strip 330 is disposed in its corresponding compartment 322 and viewable through the lid 310. Thus, the juxtaposition of the adulteration strip assembly 10 and the drug test strip 330 provides greater ease of use and viewing.

In an alternate preferred embodiment shown in FIGS. 8 and 9, the housing may comprise a cassette 400. The strip assembly 10 according to the invention may be disposed in the cassette 400 and retained by a first group of recesses 412 and projections 414. The receiving portion 53 of the absorbent strip 50 is disposed beneath a first receiving aperture 416 of the cassette 400 while the contact urinalysis pad 40 is disposed beneath an indicator aperture 418 of the cassette 400 such that the results are viewable. A drug test strip 420 is also disposed in the cassette 400 and retained by a second group of recesses 432 and projections 434. A receiving portion 441 of the drug test strip 420 is disposed beneath a second receiving aperture 451 while the indicator lines of the drug test strip 420 are disposed beneath a second indicator aperture 453.

As with the cap embodiment 300 shown in FIGS. 5 and 6, the drug test strip 420 is juxtaposed with the strip assembly 10 according to the invention in order to provide a

convenient way of viewing both results. It will be appreciated that with the receiving apertures 416, 451 placed adjacent to each other, a technician may easily place drops of the liquid sample in both apertures 416, 451 in a single motion. As with the cap embodiment 300, the side-by-side arrangement of the strip assembly 10 according to the invention and the drug test strip 420 enables a technician to easily view results with a single glance, thus obviating the need in the prior art to look at separate devices.

FIG. 10 is a flow diagram illustrating a preferred method 500 of assaying for a target substance or substances. A liquid sample is received with a reagent-free absorbent strip in step 510. Alternatively stated, the liquid sample is introduced to the absorbent strip, preferably, at a front receiving portion. In step 520, a contact detection pad is provided having dispersed therein a composition adapted to test for a substance upon contact. In step 530, the liquid sample is laterally flowed to contact the contact detection pad. The lateral flow is accomplished with the capillary action provided by the absorbent strip. If the target substance or substances to be detected are present in the liquid sample, a detectable responses is provided as result of a chemical reaction between the reagent composition and the substance or substances.

FIG. 11 is a flow diagram illustrating a method of manufacturing a combined drug testing and adulteration testing device. In step 610, a housing is provided. In a preferred method, the housing may be formed as a removable lid to a vessel, or as a cassette. In step 620, a drug test strip is disposed in the housing. The drug test strip preferably comprises a lateral flow immunoassay to test for the presence of illegal drugs. In step 630, a reagent-free absorbent strip and a contact detection pad are disposed in the housing and configured to be in communication with each other. The

contact detection pad may include a contact urinalysis pad. This is preferably accomplished with the absorbent strip directly contacting the contact detection pad. Providing a housing includes forming apertures therein that are open to the drug test strip and the absorbent strip. In step 640, fluid communication is prevented between the drug test strip, on the one hand, and the absorbent strip and adulteration pad, on the other hand. This fluid isolation of each test preserves each respective test result by preventing any contamination therebetween.

It will be appreciated that according to a preferred method of manufacturing a combination testing device, a single apparatus is provided which can perform different tests, such as detecting illegal drugs, adulterants, bodily substances and more.

Many alterations and modifications may be made by those having ordinary skill in the art without departing from the spirit and scope of the invention. Therefore, it must be understood that the illustrated embodiments have been set forth only for the purposes of example and that it should not be taken as limiting the invention as defined by the following claims. The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptionally equivalent, what can be obviously substituted and also what incorporates the essential idea of the invention.